

Q-SYS PL-CA5

Two-way, full-range 5" coaxial loudspeaker

KEY FEATURES

- Weatherized (IP54) wooden enclosure for indoor and protected outdoor environments
- Wide symmetrical coverage ideal for placement close to the listener
- Pair with Q-SYS CX-Q 4ch network amplifiers to enable custom voicings and filter sets for quicker deployment and better sonic performance
- Black (RAL 9011)



Q-SYS PL-CA5

Two-way, full-range 5" coaxial loudspeaker

The Q-SYS PL-CA5 is a two-way, full-range coaxial loudspeaker that offers wide, symmetrical coverage in a compact enclosure. It is ideal for applications when placed closer to the listener and/or where controlled coverage is not a requirement. All of the PL Series loudspeakers take advantage of the power and performance delivered by the Q-SYS Platform, including simplified setup and custom voicings, rock-solid power via Q-SYS network amplifiers, advanced telemetry, monitoring and customizable end user control.

DELIVER THE RIGHT SYSTEM FOR YOUR CUSTOMERS

PL Series loudspeakers provide an abundance of options to ensure the right loudspeaker solution anywhere in the venue that requires higher performance audio.

The PL-CA5 is a two-way, full-range coaxial loudspeaker with an HF compression driver mounted directly at the center of a 5-inch LF transducer. Coaxial drivers are designed with a compression driver mounted directly at the center of a woofer, resulting in a more compact enclosure. Several available mounting options are available to ensure these loudspeakers can be set up in the right location.

Each PL Series loudspeaker features a weatherized enclosure (IP54 rating), making them a perfect choice for indoor or protected outdoor applications. Pairing them with the Q-SYS Platform, including Q-SYS processing and network amplifiers extends several unique benefits from custom loudspeaker voicings (Intrinsic Correction™) and protection safeguards to advanced telemetry, helping to speed up deployment and deliver a more holistic system operation experience.

FULL CONTROL AND MONITORING FOR ENTERTAINMENT VENUES

The Q-SYS Platform offers a full-featured control engine that lets you deploy the right level of intuitive user control and system visibility for each stakeholder in the venue. Design an advanced system control interface with Q-SYS UCI Editor for the sound operators, containing any combination of gain, preset triggers, status indicators, telemetry data and more. Similarly, enlist Q-SYS Reflect Enterprise Manager to remotely monitor and manage the integrity of your system from anywhere, and even allow an offsite technician to identify and troubleshoot issues from any web browser.

SEAMLESS Q-SYS EXPERIENCE FOR ENTERTAINMENT VENUES AND COMPLEXES

PL Series performance loudspeakers are part of a comprehensive Q-SYS system portfolio that delivers a holistic audio, video, and control experience for the entire venue. Whether you need foreground reinforcement for your performance area, background music in the lobbies or ancillary areas, collaboration in the meeting rooms, wide area audio distribution or third-party device integration and automation, the Q-SYS Platform ties these pieces to deliver a uniquely tailored experience throughout.

Q-SYS PL-CA5

Transducers	LF: 5 in (127 mm), 1.5 in (38 mm) voice coil Coaxial tweeter 1 in (25 mm) voice coil
Enclosure configuration	Two-way, passive point source loudspeaker with bass reflex enclosure
Form factor/box angle	Asymmetrical profile, 15° between top and bottom
Coverage (horizontal x vertical)	115° conical DMT
System bandwidth¹ (no subwoofer)	-3 dB: 102 Hz - 20 kHz -6 dB: 87 Hz - 20 kHz -10 dB: 76 Hz - 20 kHz
System sensitivity²	88 dB 1 W/1 m
Max SPL (continuous)³	107 dB
Max SPL (peak)⁴	119 dB
Max SPL (calculated)⁵	114 dB
System power rating⁶	38 Vrms, continuous power 90 W @ 16 Ω, rated power 180 W @ 16 Ω
Nominal impedance	16 Ω
Minimal impedance	11.5 Ω
Enclosure material	12 mm Baltic Exterior plywood
Enclosure color	Black (RAL 9011)
Grille thickness	18 Ga, 1.2 mm
Connectors	1x Euroblock locking 4 poles 14 AWG (2.5 mm ²) The connector is recessed and may be covered by an IP65 sealing plate.
Rigging points	Rear: 2x M8, spaced 2.75 in (70 mm) Top / Bottom: 2x M8, 2.36 in (60 mm) Sides: 1x M8 for Yoke attachment
Weatherization	IP54 External plywood Stainless screws Treated grille vs. UV and corrosion Hydrophobic stainless steel mesh behind grille Polyurea Paint Input cup (IP65) sealing with gland
Recommended amplifiers	CX-Q 8K4 (up to 8 per ch) CX-Q 4K4 (up to 4 per ch) CX-Q 2K4 (up to 2 per ch)
Dimensions (HxWxD)	Net: 7.1 x 7.9 x 7.2 in (180 x 200 x 182 mm) Shipping: 9.3 x 9.5 x 9.3 in (235 x 241 x 235 mm)
Weight	Net : 50.7 lb / 23 kg Shipping: 60.8 lb / 28 kg
Accessories (sold separately)	PL-CA5-YM horizontal yoke mount PL-DC24-FM flush mount (ceiling or wall)

1. Default voicing, No sub High Pass, Smoothed

2. 1 W/1 m, Averaged on 200-10 kHz (System), 200-2 kHz (LF) or 1k-10 kHz(HF)


3. Used for simulation. Measured 1m on-axis in free space after 1mn. Pink noise 12 dB crest Factor into RMS protection, Z weight, RMS value

4. Same as Continuous SPL +12 dB CF


5. Provided for reference with former specs, Calculated from continuous noise power and sensitivity +6dB, default horn

6. Max voltage during 2 h without transducer permanent damage. Protection voltage will be lower.


Impedance




Beamwidth




Response



Horizontal Coverage



Vertical Coverage



Dimensions

