

## Q-SYS PL-DC8

### Two-way, passive 8-in point source loudspeaker

#### KEY FEATURES

- 8-in LF transducer & HF compression driver in a bass-reflex enclosure
- Weatherized (IP54) wooden enclosure for indoor and protected outdoor environments
- Reconfigurable and rotatable horn configuration enables better control over sound coverage
- Pair with Q-SYS network amplifiers and access Custom loudspeaker voicings and protection via Intrinsic Correction™
- Black (RAL 9011)



**Q-SYS PL-DC8**

Two-way, passive 8-in point source loudspeaker with directivity control

The Q-SYS PL-DC8 is a two-way passive point source loudspeaker with directivity control. It is ideal at front-of-house in a small venue, as a delay or in a distributed system in high-performance applications across entertainment, corporate, higher education or hospitality. PL Series performance loudspeakers pair a rich legacy of high-performance audio with the power and flexibility of Q-SYS to extend an integrated audio, video and control experience to your Front-of-House applications.

#### DELIVER THE RIGHT SYSTEM FOR YOUR CUSTOMERS

PL Series loudspeakers provide an abundance of options to ensure the right loudspeaker solution anywhere in the venue that requires higher performance audio.

*The PL-DC8 is a two-way, passive 8" point source loudspeaker that offers a reconfigurable and rotatable horn enabling more control over where sound needs to be heard. Each model lets you mix-and-match the horn configuration for asymmetrical coverage, while several available mounting options are available to ensure these loudspeakers can be placed in the right location.*

All of the PL Series loudspeakers feature a weatherized enclosure (IP54 rating), making them a perfect choice for indoor or protected outdoor applications. Pairing them with the Q-SYS Platform, including Q-SYS processing and network amplifiers extends a number of unique benefits from custom loudspeaker voicings (Intrinsic Correction™) and protection safeguards to advanced telemetry, helping to speed up deployment and deliver a more holistic system operation experience.

#### FULL CONTROL AND MONITORING FOR ENTERTAINMENT VENUES

The Q-SYS Platform offers a full-featured control engine that lets you deploy the right level of intuitive user control and system visibility for each stakeholder in the venue. Design an advanced system control interface with Q-SYS UCI Editor for the sound operators, containing any combination of gain, preset triggers, status indicators, telemetry data and more. Similarly, enlist Q-SYS Reflect Enterprise Manager to remotely monitor and manage the integrity of your system from anywhere, and even allow an offsite technician to identify and troubleshoot issues from any web browser.

#### SEAMLESS Q-SYS EXPERIENCE FOR ENTERTAINMENT VENUES AND COMPLEXES

PL Series are part of a comprehensive Q-SYS portfolio that lets you take advantage of industry leading power amplification, flexible AV routing, intuitive control and robust processing capabilities to deliver a singular Q-SYS experience venue-wide. Whether you need foreground reinforcement for your performance area, background music in the lobbies or ancillary areas, collaboration in the meeting rooms, wide area audio distribution or third-party device integration and automation, the Q-SYS Platform ties these pieces to deliver a uniquely tailored experience throughout.

## Q-SYS PL-DC8

<b>Transducers</b>	LF: 8 in (200 mm), 2 in (50.8 mm) voice coil, neodymium HF: Compression driver, 1 in (25.4 mm) exit, 1.75in (44.5 mm) voice coil
<b>Enclosure configuration</b>	Two-way, passive/bi-amp point source loudspeaker with bass reflex enclosure
<b>Form factor/box angle</b>	Trapezoidal, 11°
<b>Coverage (horizontal x vertical)</b>	Includes reconfigurable and rotatable half horn assemblies for flexible coverage options: <b>Symmetrical:</b> 120° x 50° (default configuration), 90° x 50° <b>Asymmetrical:</b> 105° (60° + 45°) x 50°
<b>System bandwidth<sup>1</sup> (-10dB with EQ)</b>	-3 dB: 61 Hz - 20 kHz -6 dB: 56 Hz - 20 kHz -10 dB: 51 Hz - 20 kHz
<b>Crossover HF-LF</b>	1.6 kHz (passive) 1.5 kHz (bi-amp)
<b>Sensitivity<sup>2</sup></b>	99 dB (120° x 50°) 100 dB (90° x 50°)
<b>LF Sensitivity</b>	91 dB
<b>HF Sensitivity</b>	106 dB (120° x 50°) 107 dB (90° x 50°)
<b>Max SPL (continuous)<sup>3</sup></b>	114 dB (120° x 50° passive) 116 dB (120° x 50° bi-amp) 115 dB (90° x 50° passive) 117 dB (90° x 50° bi-amp)
<b>Max SPL (peak)<sup>4</sup></b>	126 dB (120° x 50° passive) 128 dB (120° x 50° bi-amp) 127 dB (120° x 50° passive) 129 dB (120° x 50° bi-amp)
<b>Max SPL (calculated)<sup>5</sup></b>	129 dB (120° x 50° passive)
<b>Power rating<sup>6</sup></b>	46 Vrms, continuous power 260 W @ 8 Ω, rated power 520 W @ 8 Ω
<b>LF Power rating</b>	45 Vrms, continuous power 250 W @ 8 Ω, rated power 500 W @ 8 Ω
<b>HF Power rating</b>	22 Vrms, continuous power 60 W @ 8 Ω, rated power 120 W @ 8 Ω
<b>Nominal impedance</b>	8 Ω (passive), 8 Ω (LF), 16 Ω (HF)
<b>Minimal impedance</b>	6.5 Ω (passive), 6.6 Ω (LF), 13 Ω (HF)
<b>Enclosure material</b>	Exterior plywood
<b>Enclosure color</b>	Black (RAL 9011)
<b>Grille thickness</b>	18 ga, 1.2 mm
<b>Connectors</b>	2x speakON NL4 up to 10 AWG (6 mm <sup>2</sup> ). 1x Euroblock locking 4 poles (parallel to Speakon): 8 AWG (10 mm <sup>2</sup> ) The connector is recessed and may be covered by an IP65 sealing plate.
<b>Rigging points</b>	Top/ bottom: 3 x M10 Sides: 2 x M10 4 x 2.25 in (108 x 50 mm) M6 hole patterns on top, bottom and back

1. Default voicing, no sub high pass, smoothed

2. 1 W/1 m, averaged on 200-10 kHz (System), 200-2 kHz (LF) or 1k-10 kHz (HF)

3. Used for simulation. Measured 1m on-axis in free space after 1mn. Pink noise 12 dB crest Factor into RMS protection, Z weight, RMS value

4. Same as continuous SPL +12 dB CF


5. Provided for reference with former specs, calculated from continuous noise power and sensitivity +6 dB, default horn

6. Max voltage during 2 h without transducer permanent damage. Protection voltage will be lower.


# Q-SYS PL-DC8

<b>Weatherization</b>	IP54 External plywood Stainless screws Treated grille vs. UV and corrosion Hydrophobic stainless steel mesh behind grille Polyurea Paint Input cup (IP65) sealing with gland
<b>Dimensions (H x W x D)</b>	Net: 19.7 x 9.6 x 10.9 in (500 x 242 x 277 mm) Shipping: 22.3 x 15 x 15 in (565 x 380 x 380 mm)
<b>Weight</b>	Net: 26.7 lbs (12.1 kg) Shipping: 33.2 lbs (15 kg)
<b>Recommended amplifiers</b>	Q-SYS CX-Q 8K4 (up to 4 per ch) Q-SYS CX-Q 4K4 (up to 2 per ch) Q-SYS CX-Q 2K4 (up to 1 per ch)
<b>Accessories (sold separately)</b>	PL-DC8-YM horizontal yoke mount M10 KIT


### Impedance




### Beamwidth



- Horizontal 120°
- Horizontal 90°
- Vertical 50°




### Frequency




- FLAT (NO SUB)
- 125 Hz
- 100 Hz
- 80 Hz
- NO SUB

**Horizontal 90° Coverage**



**Horizontal 120° Coverage**



**Vertical 50° Coverage**

